(19) World Intellectual Property Organization

International Bureau



(43) International Publication Date 9 September 2005 (09.09.2005)

PCT

(10) International Publication Number WO 2005/083952 A1

(51) International Patent Classification7:

(21) International Application Number:

PCT/JP2005/003820

H04L 12/56

(22) International Filing Date: 28 February 2005 (28.02.2005)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 2004-056601

1 March 2004 (01.03.2004)

- (71) Applicant (for all designated States except US): MAT-SUSHITA ELECTRIC INDUSTRIAL CO., LTD. [JP/JP]; 1006, Oaza Kadoma, Kadoma-shi, Osaka, 5718501 (JP).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): YAMAGUCHI, Tsuyoshi. OHMI, Shinichiro. KURODA, Go.
- (74) Agent: OGASAWARA, Shiro; Daisan-Longev' Bldg., 3-11, Enokicho, Suita-shi, Osaka, 5640053 (JP).


- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: TERMINAL CAPABLE OF SUBSTITUTING FRAMES FOR A CONTROL STATION



(57) Abstract: A terminal of the present invention comprises a control frame detection portion of detecting a control frame issued from a control station, a control frame memory portion of storing control information contained in the control frame, a substitute frame issuance determination portion of determining to issue a substitute frame when the control frame is not detected until a predetermined first time period is elapsed, and a substitute frame issuance portion of creating a frame which is the same as or equivalent to the control frame, as the substitute frame, based on the control information stored in the control frame memory portion when the substitute frame issuance determination portion determine to issue the substitute frame, and issuing the created substitute frame.